



AUTO FEED SCREW DRIVERS
AND COLLATED FASTENERS

FLVL42- POWER DRIVER

The FLVL42 Auto Feed Screw Driver is the big brother of the FDVL42 driver. **Truck, Trailer, RV and Mezzanine floor** installs are simple tasks with 100 easy-load screw coils and easy adjustable T-handle for standup operation. The FLVL42 gets the job done fast.

- No pre-drilling required
- Adjustable depth control for repeatable countersinking
- Drives 1" to 4" screws (#10, #12 and #14)
- No more dropped or lost screws
- 100 screws per easy load coil
- Work while standing up. Less stress on back and knees
- Adjustable T-handle for the perfect standing fit
- Wood to Steel /Aluminum

Customer Support That Counts

When you work with our tools you are backed not only by the industry standard for power, speed, and quality but you have access to our extensive line of fasteners and our knowledgeable customer service staff. Pick up the phone or send an email anytime with questions about the right tools or fasteners for your job and we'll get you on the right track. Our priority is ensuring that your job gets done right.



For specifications and a full list of our tools, screws and specialized fasteners visit our web site

www.muro.com

MURO NORTH AMERICA INC.

7 Tilbury Crt., Brampton, ON., Canada L6T 3T4
productinfo@muro.com or 1 800 665 6876



FLVL42- Coil Auto Feed Screw Driving Systems

Get the Muro advantage, a simple one step process. No pre-drilling required with our systems. 100 fasteners per easy load coil. **Muro's patented Super Wing Screws are designed to ream a clearance hole so the threads do not engage in the wood. On contact with metal, reamer wings break off leaving the self drill point to drill the metal while the self threading screw pulls the wood tight to the metal.** These tools can handle many jobs, including: Bus, R.V., Trailer Floor fabrication and restoration, Wood to Steel framing, Mezzanine Floors, manufacturing of commercial vehicles such as Horse and Utility Trailers.

Specifications

Speed: 1200 RPM, 1800 RPM or 2300 RPM **Voltage:** 115V **Current:** 5.2A **Screw Range:** 1" to 4"
Accessories: Telescopic Extension Handle **Driver Bits:** *Double ended, lasts twice as long:* **SQR28118** (Square Drive #2), **SQR38000** (Square Drive #3), **PHL28118** (Phillips Drive #2), **PHL38000** (Phillips Drive #3), **TX258118** (Torx Drive #25)

Features: Adjustable depth control for countersinking, Telescopic extension handle



Visrope® Collated Screw Coils

Wood to Steel / Aluminum

Recess	Thread	Coating	Available Sizes	Application
#2 Square	Self Drill	Bright Zinc	1-1/4 - 4	Wood to Steel or Aluminum
#2 Square	Self Drill	ShieldGuard	1-1/4 - 4	Wood to Steel or Aluminum

Wood to Steel / Aluminum

Recess	Thread	Coating	Available Sizes	Application
#3 Square	Self Drill	Bright Zinc	1-1/4 - 4	Wood to Steel or Aluminum
#3 Square	Self Drill	ShieldGuard	1-1/4 - 4	Wood to Steel or Aluminum
#3 Square	Self Drill	Stainless Steel	1-3/4	Wood to Steel or Aluminum

#12 Super Wing Fasteners

Recess	Thread	Coating	Available Sizes	Application
#3 Square	Self Drill	Bright Zinc	1-1/4, 1-3/4, 2, 2-1/2, 3, 4	Wood to Steel or Aluminum

1/4" Super Wing Fasteners

Recess	Thread	Coating	Available Sizes	Application
#3 Square	Self Drill	Bright Zinc	1-3/4, 2, 2-1/2, 3, 4	Wood to Steel or Aluminum



FLVL42- Power Driver

For specifications and a full list of our tools, screws and specialized fasteners visit our web site

www.muro.com

MURO NORTH AMERICA INC.
 7 Tilbury Crt., Brampton, ON., Canada L6T 3T4
 productinfo@muro.com or 1 800 665 6876